



PAVER SHIELD

Paving Stone Sealer & Joint Sand Stabilizer

Why Paver Shield?

Provides Years of the Highest Quality Protection
Enhances the Natural Beauty of the Paver
Stain & Oil resistant • Easy to Apply
UV Stable • ASTM-E514-05 Compliant

Description

Paver Shield sealant is a thermoplastic, all acrylic polymer which seals the pavers, penetrates the jointing sand and binds the sand to the sides of the pavers creating a uniquely stabilized surface. Paver Shield is the ideal sealant for concrete paving stones, natural and manufactured stone. For concrete floors, concrete walls, retaining walls and brick walls use our Concrete Shield.

Features

- Allows pavement to retain its normal flexural qualities
- Water Repellant
- Retards Efflorescence
- Easy application
- High degree of resistance to commercial chemicals
- Unaffected by commercial de-icing salts

Benefits

- Allows pavement to retain its normal flexural qualities
- Water Repellant
- Retards Efflorescence
- Easy application
- High degree of resistance to commercial chemicals
- Unaffected by commercial de-icing salts



PAVER SHIELD


Paving Stone Sealer & Joint Sand Stabilizer

Application

- 1 Make sure the surface and **jointing sand** is THOROUGHLY DRY and free from dirt.
- 2 Remove all efflorescence prior to sealing and let dry.
- 3 Ensure that Paver Shield is only applied when there is no risk of rain within the next 8 hours.
- 4 Do not apply in extremes of temperature (below 40 F or above 110 F).
- 5 Ensure paver surface is thoroughly swept and that no jointing sand remains in the joints of the pavers.
- 6 Apply to surface of pavers liberally and spread all surpluses with a SQUEEGEE.
- 7 Accurate application rates are critical to ensure full joint stabilization (up to 200 sq ft per gallon).
- 8 Avoid walking on the sealed area for 3 hours after application and do not drive motor vehicles on the surface for 24 hours.
- 9 ALWAYS WEAR PROTECTIVE GLOVES AND GOGGLES. WEAR A MASK WHEN WORKING IN CONFINED AREAS.
- 10 All uncured spillages/splashes, and all tools must be cleaned immediately.

APPLICATION NOTE: It is recommended that you test a small area to assure satisfaction of appearance.

How it works



Excess joint sand must be removed from valley to ensure proper sealant penetration into joint

Packaging

Stock Keeping Unit (SKU #)	Size	Units per box	Units per pallet
01001	1 gal.	4	192
01005	5 gal.		36
01055	55 gal.		4
01275	275 gal.		1

First Aid

If swallowed, give large quantities of water to dilute and call a physician. In case of eye contact, rinse immediately with water for 15 to 20 minutes. For skin contact, wash thoroughly with soap and water.
KEEP FROM FREEZING - KEEP OUT OF REACH OF CHILDREN

INTERLOCK[®]
PROFESSIONAL PRODUCTS



7186 W. Gates Ave. Salt Lake City, UT 84128
877.655.8855 FAX 801.987.4101 www.interlockpro.com

Manufacturer warrants its products conform to the published specifications. No other warranty is expressed or implied. The user must determine the suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damages hereunder shall not exceed the purchased price of the product used.